

**Excellent grip in wet
and dry environments**



**Ergonomically certified
to reduce muscle effort**

FEATURES AND BENEFITS:

Comfort and Tactile Sensitivity

Soft and pliable neoprene formulation provides a more comfortable wear for longer periods, while allowing workers greater tactile sensitivity.

Secure and Confident Grip

Textured fingers ensure a strong and secure grip, while the advanced formulation helps deliver excellent wet and dry grip.

Ergonomic & Wet Grip Certified

Certified by U.S. Ergonomics for Ergonomic Design and Wet Grip. The Microflex Neogard® gloves are proven to reduce muscle effort and hand fatigue that can lead to serious injuries while enhancing gripping abilities in wet conditions.

Prevention/Protection from Type 1 Allergies

Made without natural rubber proteins and powder to help protect workers from allergies, skin irritation and dryness.

Industries

- Automotive
- Dental
- Emergency Medical Services
- Life Sciences (*Laboratory, Pharmaceutical, Biopharmaceutical & Medical Devices*)
- Manufacturing

Applications

- Biotechnologies
- Filtration processes
- Fastening, screwing & unscrewing parts
- Handling of paint/glue guns & sprayers
- Inspection and tooling precision maintenance
- Laboratory analysis and testing
- Light assembly tasks (wet & dry)
- Light duty maintenance
- Pharmaceutical manufacturing
- Picking and assembling small & medium parts
- Preparing pharmaceutical products
- Protection from blood and other bodily fluids

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	NEOGARD®
Material	Neoprene
Color	Dark Green
Glove Design	Ambidextrous, Powder-Free, Polymer Coated, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	MDD 93/42/EEC, PPED 89/686/EEC CATEGORY III, COMPLEX DESIGN, EN 455 1,2 AND 3, EN374-3, EN374-2 LEVEL 2 AQL 1.5, ASTM D6977, EN420 (SIZING FOR SPECIAL PURPOSES), REACH COMPLIANT, TGA, US QSR/FDA 510(K)
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Indonesia

PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	
Length (mm)	245	245	245	245	245	ASTM D3767/EN 420
Average Palm Width (mm)	76	86	95	106	115	
Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.10) / (mil : 3.9)					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	> 18 Mpa		> 14 Mpa			ASTM D 412-06a
Elongation at Break (%)	> 500		> 400			ASTM D 412-06a
Force at break (N)	6		6			EN 455-2

ORDERING INFORMATION:

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL
NEOGARD®	REORDER NO.	C520	C521	C522	C523	C524

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific
Ansell (Hong Kong) Limited
Unit 3102-3103, 31/F
Manhattan Place
23 Wang Tai Road
Kowloon Bay, Hong Kong
+852 2185 0600
+852 2856 2155

North America
Ansell Protective Products Inc.
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16



EN 374

EN 374

CE PPE 89/686-0493
MDD 93/42

